

BARONCELLI







ARLO TX PENDANT FACTS



MATERIALS

GLASS Cristallo rods

GLASS COLOURS




METAL FINISHES Satin gold


OTHER FINISHES Suspension cable in satin steel

WEIGHTS

Arlo TX 3333 33 kg (74 lb) Arlo TX 63 21 kg (47 lb) Arlo TX 64 22 kg (49 lb) Arlo TX 66 24 kg (54 lb)

SIZES







1040mm / 41" 1280mm / 50.5" 1520mm / 60" Arlo TX 63

800mm / 31.5"

Arlo TX 3333

1040mm / 41"

1280mm / 50.5" Arlo TX 64

1520mm / 60"



1280mm / 50.5' 1520mm / 60"

Arlo TX 66

DETAILS

SUSPENSION

Overall drop can be adjusted on site. Supplied with ceiling canopy Ø190mm (7.5") or Ø250mm (10") and 2000mm (80") of cable.

Ceiling bracket with 2 fixing slots provided (fixings not included). Ceiling bracket is suitable for use with a 3.5" octagonal junction box. Please ensure fixings and junction box are suitable to carry the weight indicated.

INSTALLATION

Fixture requires on site assembly by qualified

ELECTRICALS

LAMP

240V/120V Warm white LED tape (2600K)

Arlo TX 3333 6600Lm Arlo TX 63 4950Lm Arlo TX 64 7700Lm Arlo TX 66 66001 m

POWER

24V LED tape with power

output of: Arlo TX3333

84W Arlo TX 63 63W 70W Arlo TX 64 Arlo TX 66 84W

Supplied with 24V constant voltage mains dimmable transformers. Trailing edge dimming is recommended for best results. Transformers are housed within ceiling canopy.

Full transformer specification available upon request.

1-10v and DALI dimming options are available by request, requires an additional cable circuit to be provided, please consult your electrician for suitability.

STANDARD

All lighting is made to CE standards. LED tape and transformer UL recognised.

CONTACT US

PRODUCTION AND LOGISTICS

Via Dei Ronchi 19 Padova 35127 production@baroncelli.com

SALES OFFICES

London +44 (20) 7720 6556 New York +1 212 255 2005 studio@baroncelli.com

BARONCELLI.COM