

BARONCELLI







OTTO PENDANT FACTS



MATERIALS

GLASS Cristallo rods

GLASS COLOURS





METAL FINISHES Satin gold


WEIGHTS

2 Lights 4 kg (9 lb)

SIZES







DETAILS

SUSPENSION

Overall drop can be adjusted onsite. Supplied with ceiling canopy Ø170 (6.75") or flush mounted ceiling plate Ø100 (4") and 2000mm (79") of cable.

FIXING

Ceiling bracket with 2 fixing slots provided (fixings not included). Ceiling bracket is suitable for use with a 3.5" octagonal junction box. Please ensure fixings and junction box are suitable to carry the weight indicated.

Flush mounted ceiling plate with 2 fixing holes (screws provided) does not cover junction box.

INSTALLATION

Fixture requires on site assembly by qualified electrician.

ELECTRICALS

LAMP

240V/120V

Warm White LED tape (2600K) 1000Lm

POWER

24V LED tape with power output of 14W $\,$

Supplied with 24V constant voltage mains dimmable transformers. Trailing edge dimming is recommended for best results. Transformers are housed within ceiling canopy.

Full transformer specification available upon request.

1-10v and DALI dimming options are available by request, requires an additional cable circuit to be provided, please consult your electrician for suitability.

STANDARD

All lighting is made to CE standards. LED tape and transformer UL recognised.

CONTACT US

PRODUCTION AND LOGISTICS

Via Dei Ronchi 19 Padova 35127 production@baroncelli.com

SALES OFFICES

London +44 (20) 7720 6556 New York +1 212 255 2005 studio@baroncelli.com